TEST REPORT

IMT cellular networks; Harmonised Standard for access to radio spectrum

Part 2: CDMA Direct Spread (UTRA FDD) User Equipment (UE)

Report Reference No. ..... :	422879-2TRFWL	
Tested by (name, function and signature) ..... :	P. Barbieri	(project handler)
Approved by (name, function and signature) ..... :	D. Guarnone	(verifier)
Date of issue ..... :	2021-05-31	
Testing Laboratory ..... :	**Nemko Spa**	
Address ..... :	Via del Carroccio, 4 – 20853 Biassono (MB) – Italy	
Testing location	Nemko Spa	
Address ..... :	Via del Carroccio, 4 – 20853 Biassono (MB) – Italy	
Applicant's name ..... :	**Aesys SpA**	
Address ..... :	Via Artigiani, 41 – 24060 Brusaporto (BG) – Italy	
Test specification:		
Standard ..... :	ETSI EN 301 908-1 V13.1.1 – ETSI EN 301 908-2 V13.1.1	
	Full application of the standards	☐
	Partial application of the standards	☒
Test procedure ..... :	Nemko WM L0077, WM L0177 and WM L1002	
Test Report Form No. ..... :	301908TRFEMC	
TRF Originator ..... :	Nemko Spa	
Master TRF ..... :	2017-08	

Nemko Spa, 20853 Biassono (MB), Italy. All rights reserved.

This publication may be reproduced in whole for non-commercial purposes as long as Nemko Spa is acknowledged as copyright owner and source of the material. Nemko Spa takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description ..... :	**Monitor**
Trade Mark ..... :	aesys
Manufacturer ..... :	Aesys SpA
Address of manufacturer ..... :	Via Artigiani, 41 – 24060 Brusaporto (BG) – Italy
Code ..... :	993202033501
Model name ..... :	CPTOU4615 LS P1L3ARIO2HS24G1WTTSPFACZ0
Ratings ..... :	220 – 240 V~, 50 / 60 Hz

This test report shall not be partially reproduced without the prior written consent of Nemko S.p.A. The phase of sampling of equipment under test is carried out by the customer. Results indicated in this test report refer exclusively to the tested samples and apply to the sample as received. This Test Report, when bearing the Nemko name and logo is only valid when issued by a Nemko laboratory, or by a laboratory having special agreement with Nemko.

Test Report No. : 422879-2TRFWL	2021-05-31 Date of issue

Short description of the EuT	Copy of marking plate
The E.U.T. a information monitor provided with an internal PC. The EUT use the following separatly approved radio module: - LTE/HSPA+/GSM module SIMCom model SIM7100E-PCIE - WIFI radio module Sparklan model WUBA-171GN - PMR radio module Elancitè model NF S32-002 - Antenna type Invax model DR70 The EUT is provided also with a slim soundbar code 993301701000 (Slim Soudbar 46" MC).	

Number of tested samples:	1
Serial number:	899707
Antenna type:	External connector with dedicated antenna
Operational Frequency band:	WCDMA B1 (2100) and B8 (900)
Equipment use:	Fixed equipment
Accessories and detachable parts included:	The E.U.T. is composed of a single unit
Other options included:	--

Testing

Date of receipt of test sample:	2021-05-13
Testing commenced on:	2021-05-17
Testing concluded on:	2021-05-28

Possible test case verdicts:

test case does not apply to the test object:	N (Not applicable)
test object does meet the requirement:	P (Pass)
test object does not meet the requirement:	F (Fail)

Symbols used in this test report

☒ The crossed square indicates that the listed condition or equipment is applicable for this report.

☐ The empty square indicates that the listed condition or equipment is not applicable for this report.

Throughout this report point is used as decimal separator.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

Verdict according to the standards on page 5:	**Pass**

PROJECT HISTORY		
Report number	**Modification to the report / comments**	**Date**
422879-2TRFWL	First release	2021-05-31
--	--	--
--	--	--
--	--	--
REMARKS		
--		

PRODUCT VARIANTS		
Variant model	**Difference against the main model**	**Additional test performed**
--	--	--
--	--	--
--	--	--
--	--	--
REMARKS		
--		

Contents

1 TEST STANDARDS 5

2 SUMMARY OF TEST RESULTS 5

3 EQUIPMENT UNDER TEST 6

3.1 POWER SUPPLY SYSTEM UTILISED 6
3.2 EUT OPERATION MODES 6
3.3 EUT CONFIGURATION MODES 6
3.4 INPUT/OUTPUT PORTS 6
3.5 EQUIPMENT USED DURING TEST 7

4 TEST ENVIRONMENT 8

4.1 ADDRESS OF THE TEST LABORATORY 8
4.2 ENVIRONMENTAL CONDITIONS 8
4.3 STATEMENT OF THE MEASUREMENT UNCERTAINTY 8

5 TEST CONDITIONS AND RESULTS 10

5.1 TRANSMITTER MAXIMUM OUTPUT POWER 10
5.2 UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN 12

6 EUT PHOTOS 26

1 TEST STANDARDS

The tests were performed according to following standards and procedures.

NEMKO WM L0177: General routines for using instruments at Nemko

NEMKO WM L1002: Measurement Uncertainty - Policy and Statement

NEMKO WM L0077: General routines to perform EMC tests

ETSI EN 301 908-1 V13.1.1
IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 1: Introduction and common requirements

ETSI EN 301 908-2 V13.1.1
IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 2: CDMA Direct Spread (UTRA FDD) User Equipment (UE)

2 SUMMARY OF TEST RESULTS

Harmonized Standard ETSI EN 301 908-1				
Requirement		Requirement Conditionally		Test Result
No	Description	U/C	Condition	
1	Radiated emissions (UE)	U		P

Harmonized Standard ETSI EN 301 908-2				
Requirement		Requirement Conditionally		Test Result
No	Description	U/C	Condition	
1	Transmitter maximum output power	U		P
3	Transmitter spurious emissions	U		P

Remark: The EUT is use a separately approved radio module, so the standard has been partially applicated.

3 EQUIPMENT UNDER TEST

3.1 Power supply system utilised

Power supply voltage:	☒	230 V / 50 Hz / 1ϕ	☐	115 V / 60 Hz / 1ϕ
	☐	400 V / 50 Hz 3PE	☐	400 V / 50 Hz 3NPE
	☐	12 V DC	☐	24 V DC

3.2 EuT operation modes

Mode	Description
1	TX mode forced by a radio communication tester

3.3 EuT Configuration modes

Emission: the EuT was configured to measure its highest possible radiation level. The test modes selected are according to EuT instruction manual.

Mode	Description
1	The EUT has been connected to the mains with the Ethernet cable connected to a PC.

3.4 Input/Output Ports

Port	Name	Type*	Cable Max. >3m	Cable Shielded	Description
0	Enclosure	N/E	—	—	—
1	AC mains	AC	☒	☐	Three wires cable
2	Ethernet line	TP	☒	☒	Standard cable

*Note:

AC = AC Power Port DC = DC Power Port N/E = Non-Electrical

I/O = Signal/Control Input or Output Port TP = Telecommunication Port ANT = Antenna Port

3.5 Equipment Used During Test

Use*	Product Type	Manufacturer	Model	Comments
AE	PC	—	—	—
AE	Radio communication tester	R&S	CMW 290	—
AE	PMR Remote control	Okeenea	TX1-BUZ	—
AE	IR Remote control	Meliconi	Speedy 2 combo	—

Note: * Use

EUT - Equipment Under Test

AE - Auxiliary/Associated Equipment (Not Subjected to Test)

SIM - Simulator (Not Subjected to Test)

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

Nemko Spa
Via del Carroccio, 4
20853 Biassono (MB) – Italy

Tests site/benches are in accordance with applicable standard/s, and have been utilized under Nemko Spa testing engineer

4.2 Environmental conditions

In the laboratory, the following ambient conditions are respected for each test reported below:

Ambient temperature:	18 ÷ 33 °C (1)
Relative Humidity:	25 ÷ 70 % (2)
Atmospheric pressure:	860 ÷ 1060 hPa

(1) For luminaire, temperature during tests was verified to be within 18 ÷ 30 °C
(2) During ESD test, humidity was verified to be within 30 ÷ 60 %

The following instruments are used to monitor the environmental conditions:

Equipment	Manufacturer	Model	Serial N°
Thermo-hygrometer data loggers	Testo	175-H2	20012380/305
Thermo-hygrometer data loggers	Testo	175-H2	38203337/703
Barometer	Castle	GPB 3300	072015

4.3 Statement of the measurement uncertainty

The measurement uncertainty was calculated for each test and quantity listed in this test report, according to CISPR 16-4-2 and other specific test standard and is documented in Nemko Spa working manual WML1002.

The assessment of conformity for each test performed on the equipment is performed not taking into account the measurement uncertainty. The two following possible verdicts are stated in the report:

P (Pass) - The measured values of the equipment respect the specification limit at the points tested. The specific risk of false accept is up to 50% when the measured result is close to the limit.

F (Fail) - One or more measured values of the equipment do not respect the specification limit at the points tested. The specific risk of false reject is up to 50% when the measured result is close to the limit.

Hereafter Nemko's measurement uncertainties are reported:

EUT	Type	Test	Range	Measurement Uncertainty	Notes
Transmitter	Conducted	Frequency error	0.001 MHz ÷ 40 GHz	0.08 ppm	(1)
		Carrier power RF Output Power	0.009 MHz ÷ 30 MHz	1.1 dB	(1)
			30 MHz ÷ 18 GHz	1.5 dB	(1)
			18 MHz ÷ 40 GHz	3.0 dB	(1)
			40 MHz ÷ 140 GHz	5.0 dB	(1)
		Adjacent channel power	1 MHz ÷ 18 GHz	1.4 dB	(1)
		Conducted spurious emissions	0.009 MHz ÷ 18 GHz	3.0 dB	(1)
			18 GHz ÷ 40 GHz	4.2 dB	(1)
			40 GHz ÷ 220 GHz	6.0 dB	(1)
		Intermodulation attenuation	1 MHz ÷ 18 GHz	2.2 dB	(1)
		Attack time – frequency behaviour	1 MHz ÷ 18 GHz	2.0 ms	(1)
		Attack time – power behaviour	1 MHz ÷ 18 GHz	2.5 ms	(1)
		Release time – frequency behaviour	1 MHz ÷ 18 GHz	2.0 ms	(1)
		Release time – power behaviour	1 MHz ÷ 18 GHz	2.5 ms	(1)
		Transient behaviour of the transmitter– Transient frequency behaviour	1 MHz ÷ 18 GHz	0.2 kHz	(1)
		Transient behaviour of the transmitter – Power level slope	1 MHz ÷ 18 GHz	9%	(1)
		Frequency deviation - Maximum permissible frequency deviation	0.001 MHz ÷ 18 GHz	1.3%	(1)
		Frequency deviation - Response of the transmitter to modulation frequencies above 3 kHz	0.001 MHz ÷ 18 GHz	0.5 dB	(1)
		Dwell time	-	3%	(1)
		Hopping Frequency Separation	0.01 MHz ÷ 18 GHz	1%	(1)
		Occupied Channel Bandwidth	0.01 MHz ÷ 18 GHz	2%	(1)
		Modulation Bandwidth	0.01 MHz ÷ 18 GHz	2%	(1)
	Radiated	Radiated spurious emissions	0.009 MHz ÷ 26.5 GHz	6.0 dB	(1)
			26.5 GHz ÷ 66 GHz	8.0 dB	(1)
			66 GHz ÷ 220 GHz	10 dB	(1)
		Effective radiated power transmitter	10 kHz ÷ 26.5 GHz	6.0 dB	(1)
			26.5 GHz ÷ 66 GHz	8.0 dB	(1)
			66 GHz ÷ 220 GHz	10 dB	(1)
Receiver	Radiated	Radiated spurious emissions	0.009 MHz ÷ 26.5 GHz	6.0 dB	(1)
			26.5 GHz ÷ 66 GHz	8.0 dB	(1)
			66 GHz ÷ 220 GHz	10 dB	(1)
		Sensitivity measurement	1 MHz ÷ 18 GHz	6.0 dB	(1)
	Conducted	Conducted spurious emissions	0.009 MHz ÷ 18 GHz	3.0 dB	(1)
			18 GHz ÷ 40 GHz	4.2 dB	(1)
			40 GHz ÷ 220 GHz	6.0 dB	(1)

NOTES:
(1) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k = 2, which for a normal distribution corresponds to a coverage probability of approximately 95 %

5 TEST CONDITIONS AND RESULTS

5.1 Transmitter maximum output power

5.1.1 Photo documentation of the test set-up



5.1.2 Test method

The transmitter output power is the average value of the power delivered to an artificial antenna. The EUT has been tested connected to a spectrum analizer as specified in clause 5.3.1 of ETSI EN 301 908-2.

5.1.3 Limits

The UE maximum output power shall be within the shown value in the following table:

Operating Band	Power Class 3 (dBm)	Tolerance (dB)
1	24	+1.7
8	24	+1.7

5.1.4 Test result

Standard	Channel	RF measured (dBm)	Antenna gain (dB)	RF output power (dBm)
WCDMA B1	MID	19.6	2	21.6
WCDMA B8	MID	21.5	2	23.5

Verdict:	☒ P ☐ F ☐ N
Operation mode:	1
Configuration mode:	1
Kind of test site:	Shielded room
Remarks:	

5.1.5 Test equipment used

Equipment	Manufacturer	Model	Serial N°
EMI receiver (2 Hz ÷ 44 GHz)	R&S	ESW44	101620
Redio communication tester	R&S	CMW290	2.488
Shielded room	Siemens	Conducted emission test room	1862

5.2 Unwanted emissions in the spurious domain

5.2.1 Photo documentation of the test set-up





5.2.2 Test method

Transmitter unwanted emissions in the spurious domain are emissions outside the allocated band and outside the out-of-band domain.

For radiated emissions, the equipment was placed at the specified height on an isolated support and in the position closest to normal use as declared by the provider. The test antenna was oriented initially for vertical polarization. The output of the test antenna was connected to the measuring receiver. The transmitter was switched on with modulation. The test antenna was raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver. The measurement was repeated with the test antenna orientated for horizontal polarization.

For conducted emissions, the antenna port of the EUT was connected directly to a spectrum analyser.

5.2.3 Limits

ETSI EN 301 908-1		
Frequency range	**Minimum requirement**	**Bandwidth**
30 MHz to 1000 MHz	-36 dBm e.r.p.	100 kHz
1 GHz to 12.75 GHz	-30 dBm e.r.p.	1 MHz

ETSI EN 301 908-2		
Frequency range	**Emission limit**	**Bandwidth**
9 kHz to 150 kHz	-36 dBm.	1 kHz
150 kHz to 30 MHz	-36 dBm	10 kHz
30 MHz to 1000 MHz	-36 dBm	100 kHz
1 GHz to 12.75 GHz	-30 dBm	1 MHz

5.2.4 Test result

Verdict:	☒ P ☐ F ☐ N
Frequency range:	30 MHz to 12.75 GHz
Measurement distance:	3 m and 10 m
Kind of test site:	Semi anechoic chamber
Remarks:	

5.2.5 Test equipment used

Equipment	Manufacturer	Model	Serial N°
EMI receiver (2 Hz ÷ 44 GHz)	R&S	ESW44	101620
Trilog Antenna (25 MHz □□2 GHz)	Schwarzbeck	VULB 9162	9162-025
Bilog antenna (1 ÷ 18 GHz)	Schwarzbeck	STLP 9148-123	123
Broadband preamplifier (1 ÷ 18 GHz)	Schwarzbeck	BBV 9718	9718-137
Controller	Maturo	FCU3.0	10041
Tilt antenna mast	Maturo	TAM4.0-E	10042
Turntable	Maturo	TT4.0-5T	2.527
Semi-anechoic chamber	Nemko	10m semi-anechoic chamber	530
Shielded room	Siemens	10m control room	1947

5.2.6 Test protocol

Antenna polarization: Horizontal
Operation mode: 1
Configuration mode: 1
TX frequency: BAND 1
Frequency range: 30 MHz to 1000 MHz

Verdict: Pass



Antenna polarization: Vertical
Operation mode: 1
Configuration mode: 1
TX frequency: BAND 1
Frequency range: 30 MHz to 1000 MHz

Verdict: Pass



Antenna polarization: Horizontal
Operation mode: 1
Configuration mode: 1
TX frequency: BAND 1
Frequency range: 1 GHz to 3.6 GHz

Verdict: Pass



Limit exceeded by the carrier

Antenna polarization: Vertical
Operation mode: 1
Configuration mode: 1
TX frequency: BAND 1
Frequency range: 1 GHz to 3.6 GHz

Verdict: Pass



Limit exceeded by the carrier

Antenna polarization: Horizontal Verdict: Pass
Operation mode: 1
Configuration mode: 1
TX frequency: BAND 1
Frequency range: 3.6 GHz to 12.75 GHz



Antenna polarization: Vertical
Operation mode: 1
Configuration mode: 1
TX frequency: BAND 1
Frequency range: 3.6 GHz to 12.75 GHz

Verdict: Pass



Antenna polarization: Horizontal
Operation mode: 1
Configuration mode: 1
TX frequency: BAND 8
Frequency range: 30 MHz to 1000 MHz

Verdict: Pass



Limit exceeded by the carrier

Antenna polarization: Vertical
Operation mode: 1
Configuration mode: 1
TX frequency: BAND 8
Frequency range: 30 MHz to 1000 MHz

Verdict: Pass



Limit exceeded by the carrier

Antenna polarization: Horizontal
Operation mode: 1
Configuration mode: 1
TX frequency: BAND 8
Frequency range: 1 GHz to 3.6 GHz

Verdict: Pass



Antenna polarization: Vertical
Operation mode: 1
Configuration mode: 1
TX frequency: BAND 8
Frequency range: 1 GHz to 3.6 GHz

Verdict: Pass



Antenna polarization: Horizontal Verdict: Pass
Operation mode: 1
Configuration mode: 1
TX frequency: BAND 8
Frequency range: 3.6 GHz to 12.75 GHz



Antenna polarization: Vertical
Operation mode: 1
Configuration mode: 1
TX frequency: BAND 8
Frequency range: 3.6 GHz to 12.75 GHz

Verdict: Pass



6 EUT PHOTOS



aesys
Made in Italy
CE



End of report